



VHF MARINE TRANSCEIVER

Three Color Choices Smart Features ° ICOM IC-M25 FAV 16, CH/WX Hi/Lo SCAN Marine Blue Metallic Gray Pearl White



Slim, Lightweight, High Performance USB Charging (Micro-B USB type) 11 Hours of Battery Life



Large LCD, Simple User Interface

Float'n Flash

OPTIONAL

Optional Speaker-Microphone, HM-213



*For illustration purpose only

FEATURES

Slim, Lightweight, High Performance

The IC-M25 has the slim (depth: 30.5 mm; 1.2 in) and light (220 g; 7.8 oz) body. It also delivers uncompromised performance that will exceed expectations.

Large LCD, Simple User Interface

The IC-M25's LCD is 30% larger than its predecessor, the IC-M24 and shows clearly large channel number and status icons. The buttons on the front panel are well laid out and provide simple and straightforward operation.

USB Charging (Micro-B USB type)

A standard USB connector (Micro-B type) is used for charging the IC-M25. Cigarette lighter cables or mobile batteries for charging smartphones or other devices can be used with the IC-M25*.

* The IC-M25 accepts 5 V/1 A (Max.) input. Use of third-party products is not guaranteed.

Float'n Flash

The IC-M25 floats and lets you know where it is with the flashing red LED light and LCD/key backlight.

11 Hours of Battery Life

The built-in 1500 mAh lithium-ion battery allows 11 hours (approx.) of long operation*. * Typical operation with Tx (Hi): Rx: standby=5:5:90

Optional Speaker-Microphone, HM-213

The optional waterproof speaker-microphone, HM-213, provides commercial grade convenience while mounting the radio around the waist. The radio floats even when the HM-213 is attached.

550 mW Audio Output

The IC-M25 provides a powerful 550 mW (typical) audio output and received voice can be heard loud and clear.

Other Features

- IPX7 waterproof construction
- (1 m depth of water for 30 minutes)
- · 4-step battery life indicator
- Weather channel with weather alert
- Dual/Tri-watch functions
- Instant access to Ch 16 or programmable call channel
- Favorite channel function
- Monitor function opens noise squelch
- Auto scan function
- · LCD auto backlighting
- AquaQuake[™] prevents audio degradation from a water-logged speaker

OPTIONS Some options may not be available in some countries. Please ask your dealer for details.



SA for USA, SE for Europe plug.

GENUINE The "3D GENUINE Icom label" is attached to the rear panel.

Hologram Label Attached Check the Icom website for details: http://www.icom.co.jp/world/genuine-info/

Icom, Icom Inc. and Icom logo are registered trademarks of Icom Incorporated (Japan) in Japan, the United States, the United Kingdom, Germany, France, Spain, Russia, Australia, New Zealand and/or other countries. AQUAQUAKE is a trademark of Icom Incorporated. All other products or brands are registered trademarks or trademarks of their respective holders.

Icom Inc. 1-132, Kamiminami, Hirano-Ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013 www.icom.co.jp/world

Icom America Inc.

12421 Willows Road NE, Kirkland, WA 98034, U.S.A. Phone: +1 (425) 454-8155 Fax: +1 (425) 454-1509 E-mail: sales@icomamerica.com URL: http://www.icomamerica.com

Icom Canada

Glenwood Centre #150-6165 Highway 17A, Deita, B.C., V4K SB8, Canada Phone: +1 (604) 952-4266 Fax: +1 (604) 952-4090 E-mail: info@icomcanada.com URL: http://www.icomcanada.com

Icom Brazil

Rua Itororó, 444 Padre Eustáquio Belo Horizonte MG, CEP: 30720-450, Brazil Phone: +55 (31) 3582 8847 Fax: +55 (31) 3582 8987 F-mail: sales@icombrazil.com

Icom (Europe) GmbH

Communication Equipment Auf der Krautweide 24 65812 Bad Soden am Taunus, Germany Phone: +49 (6196) 76685-0 Fax: +49 (6196) 76685-50 E-mail: info @icomeurope.com URL: http://www.icomeurope.com

Icom Spain S.L.

Ctra. Rubi, No. 88 "Edificio Can Castanyer Bajos A 08174, Sant Cugat del Valles, Barcelona, Spain Phone: +34 (93) 590 26 70 Fax: +34 (93) 599 04 46 E-mail: icom @icomspain.com URL: http://www.icomspain.com

Icom (UK) Ltd.

Blacksole House, Altira Park, Herne Bay, Kent, CT6 6GZ, U.K. Phone: +44 (0) 1227 741741 Fax: +44 (0) 1227 741742 E-mail: info@icomuk.co.uk URL: http://www.icomuk.co.uk

Icom France s.a.s.

Zac de la Plaine, 1 Rue Brindejonc des Moulinais, BP 45804, 31505 Toulouse Cedex 5, France Phone: +33 (5) 61 36 03 03 Fax: +33 (5) 61 36 03 00 E-mail: icom@icom-france.com URL: http://www.icom-france.com

Icom (Australia) Pty. Ltd. Unit 1 / 103 Garden Road,

Clayton, VIC 3168 Australia Phone: +61 (03) 9549 7500 Fax: +61 (03) 9549 7505 E-mail: sales@icom.net.au URL: http://www.icom.net.au

SPECIFICATIONS

GENERALFrequency range RxTx 156.025–157.425 MHzUsable channel groupsINT, USA, CAN, WX channelsType of emission16K0G3E (FM)Power supply voltage3.7 V DC nominalCurrent drain Tx Rx (Internal SP/External SP)300 mA/200 mA (Max. audio)Operating temperature range-20°C to +60°C; -4°F to +140°FAntenna impedance50 Ω Dimensions (WxHxD)56.6x134.2x30.5 mm; (projections not included)2.2x5.3x1.2 inWeight (approximately)220 g; 7.8 oz (With FA-SC59V and MB-133) TRANSMITTER Output power5 W (approximately)/1 WMax. frequency deviation±5.0 kHzFrequency stability±10 ppmSpurious emissions-68 dBc typicalAdjacent channel power70 dBResidual modulation40 dB RECEIVER 70 dB typical (at 12 dB SINAD)Squelch sensitivity0.25 μ V typical (at 12 dB SINAD)Squelch sensitivity0.25 μ V typical (at 12 Ω Adjacent channel selectivityAdjacent channel selectivity70 dB typicalAudio output power550 mW typical (12 Ω load)Audio output power550 mW typical (4 Ω load)Measurements made in accordance with T1A/EIA-603. All stated specifications are subject to change without notice or obligation.Applicable IP Rating		
Rx156.050-163.275 MHzUsable channel groupsINT, USA, CAN, WX channelsType of emission16K0G3E (FM)Power supply voltage3.7 V DC nominalCurrent drain Tx2.3 ARx (Internal SP/External SP)300 mA/200 mA (Max. audio)Operating temperature range-20°C to +60°C; -4°F to +140°FAntenna impedance50 Ω Dimensions (WxHxD)56.6×134.2×30.5 mm; 2.2×5.3×1.2 inWeight (approximately)220 g; 7.8 oZ (with FA-SC59V and MB-133)THANSMITTEROutput power5 W (approximately)/1 WMax. frequency deviation±5.0 kHzFrequency stability±10 ppmSpurious emissions-68 dBc typicalAdjacent channel power70 dBResidual modulation40 dBRECEIVER70 dB typicalSpurious response70 dB typicalAdjacent channel selectivity70 dB typicalAdjacent channel selectivity70 dB typicalAudio output powerF0 dB typicalAudio output power550 mW typical (12 Ω load)Measurements made in accordance with TIA/EIA-603. All stated specifications are subject to change without notice or obligation.	GENERAL	
Usable channel groupsINT, USA, CAN, WX channelsType of emission16KOG3E (FM)Power supply voltage3.7 V DC nominalCurrent drainTxTx2.3 ARx (Internal SP/External SP)300 mA/200 mA (Max. audio)Operating temperature range-20°C to +60°C; -4°F to +140°FAntenna impedance50 Ω Dimensions (WxHxD)56.6x134.2x30.5 mm;(projections not included)2.2x5.3x1.2 inWeight (approximately)220 g; 7.8 oz(with FA-SC59V and MB-133)TFANSMITTEROutput power5 W (approximately)/1 WMax. frequency deviation±5.0 kHzFrequency stability±10 ppmSpurious emissions-68 dBc typicalAdjacent channel power70 dBResidual modulation40 dBRECEIVER25 µV typical (at 12 dB SINAD)Squelch sensitivity0.25 µV typical (at 12 dB SINAD)Squelch sensitivity0.25 µV typical (at 12 dB SINAD)Adjacent channel selectivity70 dB typicalAudio output powerIntermodulation70 dB typicalAudio output powerIntermodulation70 dB typicalAudio output power550 mW typical (4 Ω load)Measurements made in accordance with T1A/EIA-603. All statedspecifications are subject to change without notice or obligation.		
Type of emission16K0G3E (FM)Power supply voltage3.7 V DC nominalCurrent drain7xTx2.3 ARx (Internal SP/External SP)300 mA/200 mA (Max. audio)Operating temperature range-20°C to +60°C; -4°F to +140°FAntenna impedance50 Ω Dimensions (WxHxD)56.6x134.2x30.5 mm;(projections not included)2.2x5.3x1.2 inWeight (approximately)220 g; 7.8 oz(with FA-SC59V and MB-133)TRANSMITTEROutput power5 W (approximately)/1 WMax. frequency deviation±5.0 kHzFrequency stability±10 ppmSpurious emissions-68 dBc typicalAdjacent channel power70 dBResidual modulation40 dBRECEIVERSensitivity0.25 µV typical (at 12 dB SINAD)Squelch sensitivity0.25 µV typicalAdjacent channel selectivity70 dB typicalAdjacent channel selectivity70 dB typicalAudio output powerIntermodulation70 dB typicalAudioAudio output powerExternal SP300 mW typical (4 Ω load)Measurements made in accordance with T1A/EIA-603. All statedspecifications are subject to change without notice or obligation.		
Power supply voltage 3.7 V DC nominal Current drain Tx 2.3 A Tx 2.3 A 300 mA/200 mA (Max. audio) Operating temperature range -20°C to +60°C; -4°F to +140°F Antenna impedance 50 Ω Dimensions (WxHxD) 56.6x134.2x30.5 mm; (projections not included) 2.2x5.3x1.2 in Weight (approximately) 220 g; 7.8 oz (with FA-SC59V and MB-133) TRANSMITTER Output power 5 W (approximately)/1 W Max. frequency deviation ±5.0 kHz Frequency stability ±10 ppm Spurious emissions -68 dBc typical Adjacent channel power 70 dB RecelVER Sensitivity Squelch sensitivity 0.25 µV typical (at 12 dB SINAD) Squelch sensitivity 0.25 µV typical Adjacent channel selectivity 70 dB typical Audio output power To dB typical Intermodulation 70 dB typical Audio output power External SP S00 mW typical (4 Ω load) Measurements made in accordance with T1A/EIA-603. All stated specifications are subject to change without notice or obligation.		
Current drainTx2.3 ARx (Internal SP/External SP)300 mA/200 mA (Max. audio)Operating temperature range -20° C to $+60^{\circ}$ C; -4° F to $+140^{\circ}$ FAntenna impedance50 Ω Dimensions (WxHxD)56.6×134.2×30.5 mm;(projections not included)2.2×5.3×1.2 inWeight (approximately)220 g; 7.8 oz(with FA-SC59V and MB-133) TRANSMITTER Output power5 W (approximately)/1 WMax. frequency deviation ± 5.0 kHzFrequency stability ± 10 ppmSpurious emissions -68 dBc typicalAdjacent channel power70 dBResidual modulation40 dB RECEIVER Sensitivity0.25 µV typical (at 12 dB SINAD)Squelch sensitivity0.25 µV typicalAdjacent channel selectivity70 dB typicalAdjacent channel selectivity70 dB typicalAdjacent channel selectivity70 dB typicalAudio output powerIntermal SPSpurious response70 dB typicalIntermodulation70 dB typicalAudio output powerExternal SPSudiostrion)External SPSuo mW typical (4 Ω load)Measurements made in accordance with T1A/EIA-603. All statedspecifications are subject to change without notice or obligation.		. ,
Tx2.3 ARx (Internal SP/External SP)300 mA/200 mA (Max. audio)Operating temperature range -20° C to $+60^{\circ}$ C; -4° F to $+140^{\circ}$ FAntenna impedance50 Ω Dimensions (WxHxD) $56.6 \times 134.2 \times 30.5$ mm; (projections not included)2.2×5.3×1.2 inWeight (approximately)220 g; 7.8 oz (With FA-SCS9V and MB-133)TRANSMITTEROutput power5 W (approximately)/1 WMax. frequency deviation ± 5.0 kHzFrequency stability ± 10 ppmSpurious emissions -68 dBc typicalAdjacent channel power70 dBResidual modulation40 dBRecEIVERSensitivitySquelch sensitivity0.25 µV typical (at 12 dB SINAD)Squelch sensitivity0.25 µV typicalAdjacent channel selectivity70 dB typicalIntermodulation70 dB typicalAudio output powerIntermal SPSourious response70 dB typicalIntermodulation70 dB typicalAudio output power9300 mW typical (4 Ω load)Measurements made in accordance with T1A/EIA-603. All statedspecifications are subject to change without notice or obligation.	Power supply voltage	3.7 V DC nominal
Rx (Internal SP/External SP) 300 mA/200 mA (Max. audio) Operating temperature range -20° C to $+60^{\circ}$ C; -4° F to $+140^{\circ}$ F Antenna impedance 50 Ω Dimensions (W×H×D) 56.6×134.2×30.5 mm; (projections not included) 2.2×5.3×1.2 in Weight (approximately) 220 g; 7.8 oz (with FA-SC59V and MB-133) TRANSMITTER Output power 5 W (approximately)/1 W Max. frequency deviation ± 5.0 kHz Frequency stability ± 10 ppm Spurious emissions -68 dBc typical Adjacent channel power 70 dB Residual modulation 40 dB Receiver Superious (at 12 dB SINAD) Squelch sensitivity 0.25 µV typical (at 12 dB SINAD) Squelch sensitivity 0.25 µV typical Adjacent channel selectivity 70 dB typical Audio output power 70 dB ty		
$\begin{array}{r c c c c c c c c c c c c c c c c c c c$	10	
Antenna impedance 50 Ω Dimensions (W×H×D) 56.6×134.2×30.5 mm; (projections not included) 2.2×5.3×1.2 in Weight (approximately) 220 g; 7.8 oz (With FA-SC59V and MB-133) TRANSMITTER Output power 5 W (approximately)/1 W Max. frequency deviation \pm 5.0 kHz Frequency stability \pm 10 ppm Spurious emissions -68 dBc typical Adjacent channel power 70 dB Residual modulation 40 dB RECEIVER Sensitivity Squelch sensitivity 0.25 μV typical (at 12 dB SINAD) Squelch sensitivity 0.25 μV typical Adjacent channel selectivity 70 dB typical Audio output power Internal SP Stor modulation 70 dB typical Audio output power External SP 300 mW typical (4 Ω lo		, ,
Dimensions (W×H×D) 56.6×134.2×30.5 mm; (projections not included) 220 g; 7.8 oz (With FA-SC59V and MB-133) TRANSMITTER Output power 5 W (approximately)/1 W Max. frequency deviation ± 5.0 kHz Frequency stability ± 10 ppm Spurious emissions -68 dBc typical Adjacent channel power 70 dB Residual modulation 40 dB RECEIVER Sensitivity Squelch sensitivity 0.25 μV typical (at 12 dB SINAD) Squelch sensitivity 0.25 μV typical Adjacent channel selectivity 70 dB typical Adjacent channel selectivity 0.25 μV typical (at 12 dB SINAD) Squelch sensitivity 0.25 μV typical (at 12 dB SINAD) Squelch sensitivity 0.25 μV typical (at 12 dB SINAD) Adjacent channel selectivity 70 dB typical Intermodulation 70 dB typical Audio output power Intermal SP (at 10% distortion) External SP External SP 300 mW typical (4 Ω load) Measurements made in accordance with TIA/EIA-603. All stated specifications are subject to change without notice or obligation.		
(projections not included) 2.2×5.3×1.2 in Weight (approximately) 220 g; 7.8 oz (With FA-SC59V and MB-133) TRANSMITTER 0utput power Output power 5 W (approximately)/1 W Max. frequency deviation ±5.0 kHz Frequency stability ±10 ppm Spurious emissions -68 dBc typical Adjacent channel power 70 dB Residual modulation 40 dB RECEIVER Sensitivity Squelch sensitivity 0.25 μV typical (at 12 dB SINAD) Squelch sensitivity 0.25 μV typical (at 2 dB SINAD) Squelch sensitivity 0.25 μV typical (at 12 dB SINAD) Squelch sensitivity 0.25 μV typical (at 12 dB SINAD) Squelch sensitivity 0.25 μV typical (at 12 dB SINAD) Squelch sensitivity 0.25 μV typical (at 12 dB SINAD) Adjacent channel selectivity 70 dB typical Audio output power Intermodulation Audio output power Internal SP (at 10% distortion) External SP 300 mW typical (4 Ω load) Measurements made in accordacce with TIA/EIA-603. All stated specifications are subject to change without notice or obligation.		
Weight (approximately) (With FA-SC59V and MB-133) TRANSMITTER Output power 5 W (approximately)/1 W Max. frequency deviation ±5.0 kHz Frequency stability ±10 ppm Spurious emissions -68 dBc typical Adjacent channel power 70 dB Residual modulation 40 dB RECEIVER Sensitivity Squelch sensitivity 0.25 μV typical (at 12 dB SINAD) Squelch sensitivity 0.25 μV typical (at 12 dB SINAD) Squelch sensitivity 0.25 μV typical (at 12 dB SINAD) Adjacent channel selectivity 70 dB typical Audiacent channel selectivity 70 dB typical Audio output power Intermal SP Audio output power External SP 300 mW typical (4 Ω load) Measurements made in accordance with T1A/EIA-603. All stated specifications are subject to change without notice or obligation.	· /	
Weight (approximately) (With FA-SC59V and MB-133) TRANSMITTER Output power 5 W (approximately)/1 W Max. frequency deviation ±5.0 kHz Frequency stability ±10 ppm Spurious emissions -68 dBc typical Adjacent channel power 70 dB Residual modulation 40 dB RECEIVER Sensitivity Squelch sensitivity 0.25 μV typical (at 12 dB SINAD) Squelch sensitivity 0.25 μV typical (at 12 dB SINAD) Squelch sensitivity 0.25 μV typical (at 12 dB SINAD) Adjacent channel selectivity 70 dB typical Audiacent channel selectivity 70 dB typical Audio output power Intermal SP Audio output power External SP 300 mW typical (4 Ω load) Measurements made in accordance with T1A/EIA-603. All stated specifications are subject to change without notice or obligation.	Matala a sus	220 g; 7.8 oz
Output power 5 W (approximately)/1 W Max. frequency deviation ±5.0 kHz Frequency stability ±10 ppm Spurious emissions -68 dBc typical Adjacent channel power 70 dB Residual modulation 40 dB RECEIVER	vveight (approximately)	
Max. frequency deviation ±5.0 kHz Frequency stability ±10 ppm Spurious emissions -68 dBc typical Adjacent channel power 70 dB Residual modulation 40 dB RECEIVER	TRANSMITTER	
Frequency stability ±10 ppm Spurious emissions -68 dBc typical Adjacent channel power 70 dB Residual modulation 40 dB RECEIVER Sensitivity Squelch sensitivity 0.25 μV typical (at 12 dB SINAD) Squelch sensitivity 0.25 μV typical (at threshold) Adjacent channel selectivity 70 dB typical Spurious response 70 dB typical Intermodulation 70 dB typical Audio output power (at 10% distortion) Internal SP 550 mW typical (42 load) Measurements made in accordance with TIA/EIA-603. All stated specifications are subject to change without notice or obligation.	Output power	5 W (approximately)/1 W
Spurious emissions -68 dBc typical Adjacent channel power 70 dB Residual modulation 40 dB RECEIVER Sensitivity Squelch sensitivity 0.25 μV typical (at 12 dB SINAD) Squelch sensitivity 0.25 μV typical (at threshold) Adjacent channel selectivity 70 dB typical Spurious response 70 dB typical Intermodulation 70 dB typical Audio output power (at 10% distortion) Internal SP 550 mW typical (42 load) Measurements made in accordance with TIA/EIA-603. All stated specifications are subject to change without notice or obligation.	Max. frequency deviation	±5.0 kHz
Adjacent channel power 70 dB Residual modulation 40 dB RECEIVER Sensitivity Sensitivity 0.25 μV typical (at 12 dB SINAD) Squelch sensitivity 0.25 μV typical (at threshold) Adjacent channel selectivity 70 dB typical Spurious response 70 dB typical Intermodulation 70 dB typical Audio output power (at 10% distortion) Internal SP External SP 300 mW typical (4 Ω load) Measurements made in accordance with TIA/EIA-603. All stated specifications are subject to change without notice or obligation.	Frequency stability	±10 ppm
Residual modulation 40 dB RECEIVER Sensitivity 0.25 μV typical (at 12 dB SINAD) Squelch sensitivity 0.25 μV typical (at threshold) Adjacent channel selectivity 70 dB typical Spurious response 70 dB typical Intermodulation 70 dB typical Audio output power (at 10% distortion) Internal SP External SP 300 mW typical (42 load) Measurements made in accordance with TIA/EIA-603. All stated specifications are subject to change without notice or obligation.	Spurious emissions	-68 dBc typical
RECEIVER Sensitivity 0.25 μV typical (at 12 dB SINAD) Squelch sensitivity 0.25 μV typical (at threshold) Adjacent channel selectivity 70 dB typical Spurious response 70 dB typical Intermodulation 70 dB typical Audio output power (at 10% distortion) Internal SP External SP 300 mW typical (42 load) Measurements made in accordance with TIA/EIA-603. All stated specifications are subject to change without notice or obligation.	Adjacent channel power	70 dB
Sensitivity 0.25 μV typical (at 12 dB SINAD) Squelch sensitivity 0.25 μV typical (at threshold) Adjacent channel selectivity 70 dB typical Spurious response 70 dB typical Intermodulation 70 dB typical Audio output power (at 10% distortion) Internal SP External SP 300 mW typical (42 load) Measurements made in accordance with TIA/EIA-603. All stated specifications are subject to change without notice or obligation.	Residual modulation	40 dB
Squelch sensitivity 0.25 μV typical (at threshold) Adjacent channel selectivity 70 dB typical Spurious response 70 dB typical Intermodulation 70 dB typical Audio output power (at 10% distortion) Internal SP External SP 300 mW typical (4 Ω load) Measurements made in accordance with TIA/EIA-603. All stated specifications are subject to change without notice or obligation.	RECEIVER	
Adjacent channel selectivity 70 dB typical Spurious response 70 dB typical Intermodulation 70 dB typical Audio output power (at 10% distortion) Internal SP External SP 300 mW typical (12 Ω load) Measurements made in accordance with TIA/EIA-603. All stated specifications are subject to change without notice or obligation.	Sensitivity	0.25 µV typical (at 12 dB SINAD)
Spurious response 70 dB typical Intermodulation 70 dB typical Audio output power (at 10% distortion) Internal SP External SP 300 mW typical (12 Ω load) Measurements made in accordance with TIA/EIA-603. All stated specifications are subject to change without notice or obligation.	Squelch sensitivity	0.25 µV typical (at threshold)
Intermodulation 70 dB typical Audio output power (at 10% distortion) Internal SP External SP 300 mW typical (12 Ω load) Measurements made in accordance with TIA/EIA-603. All stated specifications are subject to change without notice or obligation.	Adjacent channel selectivity	70 dB typical
Audio output power (at 10% distortion) Internal SP External SP 550 mW typical (12 Ω load) Measurements made in accordance with TIA/EIA-603. All stated specifications are subject to change without notice or obligation. State	Spurious response	70 dB typical
(at 10% distribution) External SP 300 mW typical (4 Ω load) Measurements made in accordance with TIA/EIA-603. All stated specifications are subject to change without notice or obligation. Section 100 million	Intermodulation	70 dB typical
(at 10% distortion) External SP 300 mW typical (4 Ω load) Measurements made in accordance with TIA/EIA-603. All stated specifications are subject to change without notice or obligation. Section 100 mm and 100		550 mW typical (12 Ω load)
specifications are subject to change without notice or obligation.	(at 10% distortion) External SP	300 mW typical (4 Ω load)
Applicable IP Rating		
	Applicable IP Rating	

_-M25

Ingress Protection Standard

Water

IPX7 (Waterproof protection)



Your local distributor/dealer:

Count on us!